

EST-FS2835WW+W-120-24-Y

①

②

③

④

⑤

WW+W

Product Features

- 1.Energy-saving,eco-friendly,anti-UV and no optical radiation.
- 2.Warm white and white LEDs are seperated,and 2 chips in 1 for option.
- 3.High density LED per meter, excellent performance on ww+w color changing.
- 4.Common application for light font.

Tunable CCT

1800-6500
K K

Input DC Voltage

24VDC | 12VDC

LED Type

SMD2835 | SMD3528
SMD5050 | SMD2216

LED Qty.per meter


240 | 224 | 196 | 120
60

IP Index

IP20 | IP54 | IP65
IP67 | IP68


Part Number:EST-FS2835WW+W-120-24-Y

Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS2835WW+W-120-24-Y	1800-6500 K K	1650LM	<23W	3OZ




Controller

Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)



Strip length: CE:500CM UL:13.12FT




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue




AL. profiles (mm)




Part Number:EST-FS3528WW+W-240H-24-Y

Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS3528WW+W-240H-24-Y	2700-6500 K K	1400LM	<19.2W	3OZ




Controller

Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)



Strip length: CE:500CM UL:16.4FT




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)




Part Number:EST-FS3528WW+W-240-24-Y
Part Number:EST-FS3528WW+W-240-12-Y


Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS3528WW+W-240-24-Y	2700-6500 K K	1400LM	<19.2W	3OZ



Controller	
Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)



Strip length: CE:500CM UL:16.4FT(24V) | 9.85FT(12V)




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)




Part Number:EST-FS3528WW+W-120-24-Y


Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS3528WW+W-120-24-Y	2700-6500 K K	700LM	<9.6W	3OZ



Controller	
Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)




Strip length: CE:500CM UL:32.8FT




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue




AL. profiles (mm)




Part Number:EST-FS3528WW+W-120H-24-Y
Part Number:EST-FS3528WW+W-120H-12-Y


Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS3528WW+W-120H-24-Y	2700-6500 K K	1600LM	<19.2W	3OZ
EST-FS3528WW+W-120H-12-Y	2700-6500 K K	1400LM	<17.0W	3OZ



Controller	
Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)



Strip length: CE:500CM UL:32.8FT(24V) | 11.48FT(12V)




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)




Part Number:EST-FS5050WW+W-60H-24-Y
Part Number:EST-FS5050WW+W-60H-12-Y


Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS5050WW+W-60H-24-Y	2700-6500 K K	920LM	<14.4W	3OZ
EST-FS5050WW+W-60H-12-Y	2700-6500 K K	920LM	<14.4W	3OZ



Controller	
Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)




Strip length: CE:500CM UL:22.97FT(24V) | 13.12FT(12V)




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)




Part Number:EST-FS2216WW+W-240-24-Y

Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS2216WW+W-240-24-Y	2100K-3000K (Dimmer to warm)	550LM	<14.4W	3OZ




Controller

Product No.	Description
4.02.125-2	Dimmer (PWM) 12VDC/24VDC optional 12V<72W/24V<144W 6A*1CH



Strip length: CE:500CM UL:16.4FT




IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)




Part Number:EST-FS2216WW+W-196-24-Y

Model	Tunable CCT	LM/M	Power/M	FPC copper
EST-FS2216WW+W-196-24-Y	1800-6500 K K	1100LM	<12W	3OZ




Controller

Product No.	Description
4.02.128	12-24VDC 3A*2CH Max.6A 72W/144W(12V/24V)



Strip length: CE:500CM UL:16.4FT



IP Rating:

- ☒ IP20---Non waterproof
- ☒ IP54---Nano coated
- ☒ IP65---Silicon coated
- ☒ IP67---Silicon coated & Wrapped heat shrink tube
- ☒ IP67---PVC extrusion
- ☒ IP67---Silicon extrusion
- ☒ IP67---Silicon tube(transparent)
- ☒ IP68---Silicon tube(transparent) & Inject silicon glue



AL. profiles (mm)

